



a GFL product

gflenv.com

eco-freez.com

Ecofreez Global Premium Coolant provides the following advantages:

- Extended service up to 5 years or 250,000km
- Freeze protection to -37C and boil-over to 129C at a 50/50 vol.% dilution
- Add as a top-up to any colour antifreeze
- Recommended for use in all makes and models of foreign and domestic passenger vehicles and light duty trucks
- Protects coolant system metals such as brass, copper, solder, steel, cast iron and aluminum
- Low silicate and phosphate free
- Contains Bitrex, a bittering agent that makes the antifreeze less appealing to animals and children
- Pre-mixed with de-ionized water

Ecofreez Global Coolant meets the following industry performance requirements:

- ASTM D3306
- Japanese Standard JIS K2234

Recommended for use with:

- Any colour car or light duty truck coolant

GLOBAL PREMIUM COOLANT

Ecofreez Global Premium Coolant is a superior, extended life, reclaimed, ethylene glycol based engine coolant. It is recommended for use in all makes and models of foreign and domestic passenger vehicles and light duty trucks.

It contains proprietary formulation of premium corrosion inhibitors as well as extended protection from corrosion, rust and pitting caused by cavitation for all coolant system metals.

It does not promote colour change when used as a top up to any colour antifreeze.

This product provides up to 5 years or 250,000km of protection after a complete drain, flush and fill.



Typical Product Properties

Characteristics	Performance	Test Method
pH	7.6 – 8.5	ASTM D1287
Specific gravity*	1.070 – 1.090	ASTM D1122
Freeze point, °C/°F	-37/-34	ASTM D1177
Foam volume, ml	150 max.	ASTM D1881
Foam break time, second	5 max.	ASTM D1881
Reserve Alkalinity, ml	1.8 min.	ASTM D1121
Chloride, ppm	25 max.	ASTM D3634
Colour	Pale Yellow	
Glycol Content (wtg.%)	53 min.	
Inhibitors and Water Content (wtg.%)	47 max.	
Silicon (ppm)	< 10	ASTM D6130
Boron (ppm)	< 10	
Phosphorous	< 10	

* Measured at 15.6°C/60°F